



US010001009B2

(12) **United States Patent**
Bower et al.

(10) **Patent No.:** **US 10,001,009 B2**
(45) **Date of Patent:** ***Jun. 19, 2018**

(54) **PUMPABLE MINE VENTILATION
STRUCTURE**

E21F 17/107 (2006.01)
E21D 11/00 (2006.01)

(Continued)

(71) Applicants: **Heintzmann Corporation**, Cedar Bluff,
VA (US); **ABC Industries, Inc.**,
Warsaw, IN (US)

(52) **U.S. Cl.**
CPC *E21F 7/00* (2013.01); *E21D 11/003*
(2013.01); *E21D 11/04* (2013.01); *E21D 13/00*
(2013.01); *E21F 1/14* (2013.01); *E21F 17/107*
(2013.01)

(72) Inventors: **Joseph P. Bower**, Morgantown, WV
(US); **John J. Breedlove**, Cedar Bluff,
VA (US); **Erik Denver**, Keen
Mountain, VA (US); **Steven S. Fleagle**,
Syracuse, IN (US); **Tyler Proffitt**,
Pounding Mill, VA (US)

(58) **Field of Classification Search**
USPC 405/132, 151, 288, 289; 299/11, 12;
454/168, 169, 170
See application file for complete search history.

(73) Assignees: **FCI Holdings Delaware, Inc.**,
Wilmington, DE (US); **ABC Industries,
Inc.**, Winona Lake, IN (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,937,025 A * 2/1976 Alvarez-Calderon
F. *E21F 15/04*
299/11
6,082,828 A * 7/2000 Bailey *E21F 17/103*
299/12

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days. days.

This patent is subject to a terminal dis-
claimer.

OTHER PUBLICATIONS

http://www.dictionary.com/browse/weep.*

Primary Examiner — Sean D Andrish

(74) *Attorney, Agent, or Firm* — The Webb Law Firm

(21) Appl. No.: **14/627,058**

(22) Filed: **Feb. 20, 2015**

(65) **Prior Publication Data**

US 2016/0245082 A1 Aug. 25, 2016

Related U.S. Application Data

(62) Division of application No. 14/174,984, filed on Feb.
7, 2014, now Pat. No. 9,022,689.

(60) Provisional application No. 61/854,223, filed on Apr.
19, 2013, provisional application No. 61/846,698,
filed on Jul. 16, 2013.

(51) **Int. Cl.**
E21D 15/00 (2006.01)
E21F 7/00 (2006.01)
E21F 1/14 (2006.01)

(57) **ABSTRACT**

A pumpable mine ventilation stopping wall structure com-
prised of a pumpable bag having spaced walls of generally
parallel nonporous and flexible sheets with the sheets
retained in spaced relationship with spaced flexible cross
ties. The perimeter of the spaced walls may be closed off
with a permeable mesh having a mesh size which will permit
restricted flow of cementitious grout therethrough for seal-
ing the wall structure to surrounding rough mine faces. The
bag is provided with at least one grout fill port for filling the
bag by pumping cementitious grout into the bag.

2 Claims, 7 Drawing Sheets

